DIF® FAST-ACTING WALLPAPER STRIPPER

DESCRIPTION AND USES

Zinsser ® DIF® Fast-Acting Wallpaper Stripper is a fast acting, all purpose formula which is non-toxic and non-staining. It is excellent for removing stubborn, old wallcoverings quickly. It will effectively remove 75 square feet of wallpaper per 32 ounce spray and 300 square feet per gallon in minutes.

PRODUCTS

SKU	Description
2486	32 Fluid Ounces
2481	1-Gallon

PRODUCT APPLICATION

SURFACE PREPARATION

Spread a solvent resistant drop cloth covered with newspapers around the work area in case of drips and spills. Protect carpeting, furniture and porous ceilings before application. Protect eyes and skin. Wear safety goggles and chemical resistant gloves.

PRODUCT APPLICATION (cont.)

Note: Ensure good cross ventilation during application. Wear a NIOSH approved respirator when spraying.

APPLICATION

Spray on or sponge apply DIF Fast-Acting on the wallpaper surface. Do not use a fine mist sprayer. Protect adjacent areas from overspray. Wait 5-10 minutes and scrape off loose wallpaper with the Paper Scraper™. If the top layer does not peel off easily, score (10 holes per square inch) with Paper Tiger™ and apply more DIF Fast-Acting Wallpaper Stripper. Allow DIF to penetrate for 5-10 additional minutes. Repeat the removal process and re-apply the stripper if necessary. To remove residual adhesive, re-apply the DIF solution, wait 5-10 minutes and scrape or sponge off. Rinse with clean water. **KEEP OUT OF REACH OF CHILDREN.**

SPILLAGE

If spilled, contain spilled material and remove with an inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations. Clean up rags, papers and waste promptly.

CLEAN-UP

Clean up tools and equipment with soap and water.

Form: GDH-210
Rev.: 102813

TECHNICAL DATA

DIF® FAST-ACTING WALLPAPER STRIPPER

PHYSICAL PROPERTIES

Physical Properties		FAST-ACTING READY-TO-USE WALLPAPER STRIPPER
Composition		Modified Anionic Thickener, Glycol Ether, Water
Weight	**Per Gallon**	8.3 lbs.
	Per Liter	1.00 kg
Volatile Organic Compounds		360 g/l
Practical Coverage		Varies with porosity of wallpaper
Shelf Life		5 years
Flash Point		200ºF (93°C)
Caution!		Avoid contact with eyes and skin. If eye contact occurs, flush with water for at least 15 minutes. If irritation persists, seek medical attention. Do not take internally. **KEEP OUT OF REACH OF CHILDREN.**
Safety Information		For additional information, see MSDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.

RUST-OLEUM BRANDS

Rust-Oleum Corporation
11 Hawthorn Parkway
Vernon Hills, Illinois 60061
An RPM Company

Phone: 877•385•8155
www.rustoleum.com

Form: GDH-210
Rev.: 102813